

Transducers For Bottom Discrimination Functionality

Transducer	Description	FCV627/628	FCV587/588	BBDS1	Manufacturer
520-5PSD	600W Plastic Thru-Hull	✓	✓	✓	Furuno
520-5MSD	600W Bronze Thru-Hull	✓	✓	✓	Furuno
520-PLD	600W Plastic Thru-Hull	✓	✓		Airmar
525-5PWD	600W Plastic Transom Mount	✓	✓	✓	Furuno
525T-PWD	600W Plastic Transom Mount w/temp	✓	✓		Airmar
525T-BSD	600W Bronze Thru-Hull w/Temp	✓	✓		Airmar
525T-LTD/12	600W Bronze TH LP 12° w/Temp	✓	✓		Airmar
525T-LTD/20	600W Bronze TH LP 20° w/Temp	✓	✓		Airmar
525STID-MSD	600W Bronze TH Multi-Sensor	✓	✓	✓	Airmar
525STID-PWD	600W Plastic TM Multi-Sensor	✓	✓	✓	Airmar
SS60-SLTD/12	600W Stainless Steel LP 12°	✓	✓		Airmar
SS60-SLTD/20	600W Stainless Steel LP 20°	✓	✓		Airmar
CA50/200-1T*	1kW Rubber Coated		✓	✓	Furuno
CA50/200-12M*	1kW Bronze Thru-Hull		✓	✓	Furuno
526TID-HDD	1KW Bronze Broadband w/Temp		✓		Airmar

*MB1100 is a Required Option

Bottom discrimination operating environment: Depth 16 to 328 Feet, Speed 10 knots or less